

Davenport Collection

Specifications



Davenport Collection Specifications

 Construction: Engineered High Density Ply Core Hardwood with Tongue and Groove	 Edge Profile: 1-2mm Micro Beveled Edges and Ends
 Species: Hickory	 Installation: Nail, Staple, Glue, Float; Above Grade, At Grade, Below Grade
 Dimensions: 3/8" (Nominal Overall Thickness) X 7 1/2" (widths) X 15"-60"	 Surface Treatment: Wire Brushed
 Thickness of Surface Layer: 1.2mm	 Gloss: <10 degree
 Cutting Method: Slice	 Moisture Content: 6%–9%
 Grade: ABCDE	 Color Variation: Apparent Color Variation, Water Based Color

Finish:

8 coats of Enhanced Ultra Low Gloss Urethane finish with advanced aluminum oxide technology. Color depth through smoking and aging multi-step treatment and hand stained for weathered patina. On-trend colors.

Assembling Gap: $\leq 0.20\text{mm}$

Length Deviation: $\pm 0.5\text{mm}$

Width Deviation: $\pm 0.15\text{mm}$

Thickness Deviation: $\pm 0.2\text{mm}$

Reactive Stain: Yes

Surface Abrasion Resistance: $\geq 300\text{r}$, S-42 Sand paper

Film Hardness: $\geq 2\text{H}$

Static Bending Strength: $\geq 30\text{MPa}$



Packaging

Area per carton: 34.36 Sqft. per Carton

Weight per carton: 45.75 Lbs

Warranties: 50 year residential finish warranty, 5 year commercial warranty. Please visit www.palmettoroadfloors.com for the most current warranty information.



Environmental

Certifications: Floor Score Certified

Carb II Compliant: Yes

Lacy Act Compliant: Yes