

Hampton Meadows

Specifications



Hampton Meadows Specifications

 Construction: Engineered High Density Ply Core Hardwood with Tongue and Groove	 Edge Profile: 1.8-2.2mm Micro Beveled Edges and Ends
 Species: French Oak	 Installation: Nail, Staple, Glue, Float; Above Grade, At Grade, Below Grade
 Dimensions: 9/16" (Nominal Overall Thickness) X 6 1/2" (width) X 15"-74.8" (Varying Lengths)	 Surface Treatment: 3D grain visual remained
 Thickness of Surface Layer: 4mm	 Gloss: 4±2degree
 Cutting Method: Sawn	 Moisture Content: 6%-9%
 Grade: ABCDE	

Finish:
UV/6 primer² finish, Sherwin-Williams+overmat.

Assembling Gap: ≤0.20mm

Length Deviation: ±0.5mm

Width Deviation: ±0.15mm

Thickness Deviation: ±0.2mm

Reactive Stain: No

Surface Abrasion Resistance: ≥300r,S-33Sand paper

Film Hardness: ≥2H

Static Bending Strength: No

Moisture Content: 6%-9%



Packaging

Area per carton: 20.25 Sqft. per Carton

Weight per carton: 39.46 Lbs

Warranties: 50 year residential finish warranty, 5 year commercial warranty. Please visit www.palmettoroadfloors.com for the most current warranty information.



Environmental

Certifications: Floor Score Certified

Carb II Compliant: Yes

Lacy Act Compliant: Yes