Chalmers Collection

Specifications



Chalmers Collection Specifications



Construction:

Engineered High Density Ply Core Hardwood with Tongue and Groove



Edge Profile: 1-2mm Micro Beveled Edges and Ends



Species:

French Oak



Installation: Nail, Staple, Glue, Float; Above Grade, At Grade, Below Grade



Dimensions:

1/2" (Nominal Overall Thickness) X 7 1/2" (width) X 72" (Varying Lengths)



Surface Treatment:

Bevel hand scrape+brush



Thickness of Surface Layer:

2mm



Gloss: 8±3degree



Cutting Method:

Sliced Face



Moisture Content: 6%-9%



Grade: CDEF

Finish:

UV/6 primer2 finish, Sherwin-Williams.

Assembling Gap: ≤0.20mm **Length Deviation:** ±0.5mm **Width Deviation:** ±0.15mm

Thickness Deviation: ±0.2mm

Reactive Stain: No

Surface Abrasion Resistance: ≥300r,S-33Sand paper

Film Hardness: ≥2H

Static Bending Strength: ≥30MPa

Moisture Content: 6%-9%



Packaging

Area per carton: 22.82 Sqft. per Carton

Weight per carton: 38 Lbs

Warranties: 50 year residential finish warranty. 5 year commercial warranty. Please visit www.palmettoroadfloors.com for the most current warranty information.



Environmental

Certifications: Floor Score Certified

Carb II Compliant: Yes **Lacy Act Compliant:** Yes