Middleton Collection

Specifications



Middleton Collection Specifications



Construction:

Engineered High Density Ply Core Hardwood with Tongue and Groove



Edge Profile: 1-2mm Micro Beveled Edges and Ends



Species:

French Oak



Installation: Nail, Staple, Glue, Float; Above Grade, At Grade, Below Grade



Dimensions:

3/8" (Nominal Overall Thickness) X 7 1/2" (widths) X 15"-60"



Surface Treatment:

Wire Brushed



Thickness of Surface Layer:

1.5mm



Gloss: <10 degree



Cutting Method:

Slice



Moisture Content: 6%-9%



Grade:

ABCDE



Color Variation:

Apparent Color Variation, Water Based Color

Finish:

8 coats of Enhanced Ultra Low Gloss Urethane finish with advanced aluminum oxide technology. Color depth through smoking and aging multi-step treatment and hand stained for weathered patina. On-trend colors.

Assembling Gap: ≤0.20mm **Length Deviation:** ±0.5mm **Width Deviation:** ±0.15mm

Thickness Deviation: ±0.2mm

Reactive Stain: Yes

Surface Abrasion Resistance: ≥300r, S-42 Sand paper

Film Hardness: ≥2H

Static Bending Strength: ≥30MPa



Packaging

Area per carton: 34.36 Sqft. per Carton

Weight per carton: 45.75 Lbs

Warranties: 50 year residential finish warranty. 5 year commercial warranty. Please visit www.palmettoroadfloors.com for the most current warranty information.



Environmental

Certifications: Floor Score Certified

Carb II Compliant: Yes **Lacy Act Compliant:** Yes