

Monet Collection

Specifications



Monet Collection Specifications

 Construction: Engineered High Density Ply Core Hardwood with Tongue and Groove	 Edge Profile: 1.5-2mm Micro Beveled Edges and Ends
 Species: French Oak	 Installation: Nail, Staple, Glue, Float; Above Grade, At Grade, Below Grade
 Dimensions: 3/8" (Nominal Overall Thickness) X 6 1/2" (width) X 15"-60" (Varying Lengths)	 Surface Treatment: Wire Brushed
 Thickness of Surface Layer: 1.2mm	 Gloss: <10 degree
 Cutting Method: Sliced Face	 Fire Testing ASTM E648 and ASTM E662 Results: Class I ASTM E84 Result: Class B
 Grade: ABCD	 Color Variation: Moderate Color Variation, Water Based Color

Finish:

8 coats of Enhanced Ultra Low Gloss Urethane finish with advanced aluminum oxide technology. On-trend colors.

Assembling Gap: $\leq 0.20\text{mm}$

Length Deviation: $\pm 0.5\text{mm}$

Width Deviation: $\pm 0.15\text{mm}$

Thickness Deviation: $\pm 0.2\text{mm}$

Reactive Stain: No

Surface Abrasion Resistance: $\geq 300\text{r}$, S-42 Sand paper

Film Hardness: $\geq 2\text{H}$

Static Bending Strength: $\geq 30\text{MPa}$

Moisture Content: 6%-9%



Packaging

Area per carton: 22.38 Sqft. per Carton

Weight per carton: 29.76 Lbs

Warranties: 50 year residential finish warranty, 5 year commercial warranty. Please visit www.palmettoroadfloors.com for the most current warranty information.



Environmental

Certifications: Floor Score Certified

Carb II Compliant: Yes

Lacy Act Compliant: Yes